# Audience AP Fixed Drops — 12/3 → NL4

**Wire diagram · 3 drops (NJCT 5/6/7) · lengths pending verify · KG3 · BEA 2026 (Beabadoobee Headline Tour) · rev Aug 31, 2026**

**What it is:** fixed power drop at each audience chain-motor pickup (AP 1/2/3 = PWR-NJCT 5/6/7). **12/3 SOOW** from the flown PWR-NJCT down to the rope, lashed to the black pickup cable, terminated on **NL4**. Power only — **no data on any drop**; the NL4 data pin stays EMPTY.

## Pin map (Chance's drop standard: two +24V legs + shared negative)

| 12/3 CONDUCTOR (TYPICAL) | NL4 PIN | FUNCTION |
|---|---|---|
| Black | **1+** | +24V leg 1 |
| Red | **2+** | +24V leg 2 |
| White | **1–** | shared GND (V–) |
| — | **2–** | EMPTY — no data on drops, cap and label |

## Lengths — DO NOT CUT YET

| DROP | POSITION | WORKING LENGTH (UNVERIFIED) |
|---|---|---|
| **NJCT 5** | AP1 chain motor | 26'0" + tails |
| **NJCT 6** | AP2 chain motor | 30'0" + tails |
| **NJCT 7** | AP3 chain motor | 28'10" + tails |

> **Lengths are per Sheet 4.11 and NOT laser-verified.** Wait for confirmed trim heights before cutting. 3 drops total, 12/3 SOOW, one gauge everywhere on this job (decision Aug 31). Custom length = GOLD tape.