

PIECE DETAIL REPORT

BBDB

Client: 1826 Touring (Wilkie Wilkinson / Connor Houston)
Product: KG3 LumiRope 360 HD 22mm Black (LEDODM NL-Ws2811-120-D22) | SKU: LUMIROPE-360-22-BLK
Cut Increment: 50mm | Voltage: 24V | IP: IP67 | Reel Cap: 10,000mm
Total Pieces: 33 | Reels: 0 | Generated: 9/2/2026

#	FIXTURE	LENGTH	INCHES	PIXELS	WATTS	CONNECTOR	REEL	STATUS
1	DS1-1	9,150 mm	360.2"	183	210.8W	NL4	--	DEFINED
2	DS1-2	9,300 mm	366.1"	186	214.3W	NL4	--	DEFINED
3	DS2-1	9,150 mm	360.2"	183	210.8W	NL4	--	DEFINED
4	DS2-2	9,300 mm	366.1"	186	214.3W	NL4	--	DEFINED
5	DS3-1	9,150 mm	360.2"	183	210.8W	NL4	--	DEFINED
6	DS3-2	9,300 mm	366.1"	186	214.3W	NL4	--	DEFINED
7	US4-1	8,650 mm	340.6"	173	199.3W	NL4	--	DEFINED
8	US4-2	6,700 mm	263.8"	134	154.4W	NL4	--	DEFINED
9	US5-1	8,650 mm	340.6"	173	199.3W	NL4	--	DEFINED
10	US5-2	6,700 mm	263.8"	134	154.4W	NL4	--	DEFINED
11	US6-1	8,650 mm	340.6"	173	199.3W	NL4	--	DEFINED
12	US6-2	6,700 mm	263.8"	134	154.4W	NL4	--	DEFINED
13	USR1-1	4,900 mm	192.9"	98	112.9W	NL4	--	DEFINED
14	USR1-2	4,900 mm	192.9"	98	112.9W	NL4	--	DEFINED
15	USR1-3	4,900 mm	192.9"	98	112.9W	NL4	--	DEFINED
16	USR2-1	5,000 mm	196.9"	100	115.2W	NL4	--	DEFINED
17	USR2-2	5,000 mm	196.9"	100	115.2W	NL4	--	DEFINED
18	USR2-3	5,000 mm	196.9"	100	115.2W	NL4	--	DEFINED
19	AUD1-1	8,000 mm	315.0"	160	184.3W	NL4	--	DEFINED
20	AUD1-2	10,200 mm	401.6"	204	235W	NL4	--	DEFINED
21	AUD1-3	10,200 mm	401.6"	204	235W	NL4	--	DEFINED
22	AUD2-1	8,300 mm	326.8"	166	191.2W	NL4	--	DEFINED
23	AUD2-2	10,250 mm	403.5"	205	236.2W	NL4	--	DEFINED
24	AUD2-3	10,200 mm	401.6"	204	235W	NL4	--	DEFINED
25	SPARE-5M-1 *	5,000 mm	196.9"	100	115.2W	NL4	--	DEFINED
26	SPARE-5M-2 *	5,000 mm	196.9"	100	115.2W	NL4	--	DEFINED
27	SPARE-5M-3 *	5,000 mm	196.9"	100	115.2W	NL4	--	DEFINED
28	SPARE-10M-1 *	10,000 mm	393.7"	200	230.4W	NL4	--	DEFINED
29	SPARE-10M-2 *	10,000 mm	393.7"	200	230.4W	NL4	--	DEFINED
30	SPARE-10M-3 *	10,000 mm	393.7"	200	230.4W	NL4	--	DEFINED
31	SPARE-11M-1 *	11,000 mm	433.1"	220	253.4W	NL4	--	DEFINED
32	SPARE-11M-2 *	11,000 mm	433.1"	220	253.4W	NL4	--	DEFINED
33	SPARE-11M-3 *	11,000 mm	433.1"	220	253.4W	NL4	--	DEFINED
TOTALS		266,250 mm	10482.3"	5325	6134.4W			

PIECE DETAILS

DS1-1

Status: DEFINED

Length: 9,150 mm (360.2")

File: 9144 mm | Rounded: 9150 mm

Pixels: 183

Power: 210.8W / 8.78A @ 24V

Cut Increment: 50mm

Input: NL4

Output: XLR 5-Pin

Cable: 12"

Location: CTRL A · Out 1 · DS1

Side: seg 1 of 2

Type: Pixel rope segment

Reel: Unassigned

DS1-2

Status: DEFINED

Length: 9,300 mm (366.1")

File: 9296 mm | Rounded: 9300 mm

Pixels: 186

Power: 214.3W / 8.93A @ 24V

Cut Increment: 50mm

Input: NL4

Output: XLR 5-Pin

Cable: 12"

Location: CTRL A · Out 1 · DS1

Side: seg 2 of 2

Type: Pixel rope segment

Reel: Unassigned

DS2-1

Status: DEFINED

Length: 9,150 mm (360.2")

File: 9144 mm | Rounded: 9150 mm

Pixels: 183

Power: 210.8W / 8.78A @ 24V

Cut Increment: 50mm

Input: NL4

Output: XLR 5-Pin

Cable: 12"

Location: CTRL A · Out 2 · DS2

Side: seg 1 of 2

Type: Pixel rope segment

Reel: Unassigned

DS2-2

Status: DEFINED

Length: 9,300 mm (366.1")

File: 9296 mm | Rounded: 9300 mm

Pixels: 186

Power: 214.3W / 8.93A @ 24V

Cut Increment: 50mm

Input: NL4

Output: XLR 5-Pin

Cable: 12"

Location: CTRL A · Out 2 · DS2

Side: seg 2 of 2

Type: Pixel rope segment

Reel: Unassigned

DS3-1

Status: DEFINED

Length: 9,150 mm (360.2")

File: 9144 mm | Rounded: 9150 mm

Pixels: 183

Power: 210.8W / 8.78A @ 24V

Cut Increment: 50mm

Input: NL4

Output: XLR 5-Pin

Cable: 12"

Location: CTRL A · Out 3 · DS3

Side: seg 1 of 2

Type: Pixel rope segment

Reel: Unassigned

DS3-2

Status: DEFINED

Length: 9,300 mm (366.1") File: 9296 mm | Rounded: 9300 mm
Pixels: 186 Power: 214.3W / 8.93A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL A · Out 3 · DS3 Side: seg 2 of 2 Type: Pixel rope segment
Reel: Unassigned

US4-1

Status: DEFINED

Length: 8,650 mm (340.6") File: 8636 mm | Rounded: 8650 mm
Pixels: 173 Power: 199.3W / 8.30A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL B · Out 1 · US4 Side: seg 1 of 2 Type: Pixel rope segment
Reel: Unassigned

US4-2

Status: DEFINED

Length: 6,700 mm (263.8") File: 6655 mm | Rounded: 6700 mm
Pixels: 134 Power: 154.4W / 6.43A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL B · Out 1 · US4 Side: seg 2 of 2 Type: Pixel rope segment
Reel: Unassigned

US5-1

Status: DEFINED

Length: 8,650 mm (340.6") File: 8636 mm | Rounded: 8650 mm
Pixels: 173 Power: 199.3W / 8.30A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL B · Out 2 · US5 Side: seg 1 of 2 Type: Pixel rope segment
Reel: Unassigned

US5-2

Status: DEFINED

Length: 6,700 mm (263.8") File: 6655 mm | Rounded: 6700 mm
Pixels: 134 Power: 154.4W / 6.43A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL B · Out 2 · US5 Side: seg 2 of 2 Type: Pixel rope segment
Reel: Unassigned

US6-1

Status: DEFINED

Length: 8,650 mm (340.6") File: 8636 mm | Rounded: 8650 mm
Pixels: 173 Power: 199.3W / 8.30A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL B · Out 3 · US6 Side: seg 1 of 2 Type: Pixel rope segment
Reel: Unassigned

US6-2

Status: DEFINED

Length: 6,700 mm (263.8") File: 6655 mm | Rounded: 6700 mm
Pixels: 134 Power: 154.4W / 6.43A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL B · Out 3 · US6 Side: seg 2 of 2 Type: Pixel rope segment
Reel: Unassigned

USR1-1

Status: DEFINED

Length: 4,900 mm (192.9") File: 4877 mm | Rounded: 4900 mm
Pixels: 98 Power: 112.9W / 4.70A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL C · Out 1 · USR1 Side: seg 1 of 3 Type: Pixel rope segment
Reel: Unassigned

USR1-2

Status: DEFINED

Length: 4,900 mm (192.9") File: 4877 mm | Rounded: 4900 mm
Pixels: 98 Power: 112.9W / 4.70A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL C · Out 1 · USR1 Side: seg 2 of 3 Type: Pixel rope segment
Reel: Unassigned

USR1-3

Status: DEFINED

Length: 4,900 mm (192.9") File: 4877 mm | Rounded: 4900 mm
Pixels: 98 Power: 112.9W / 4.70A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL C · Out 1 · USR1 Side: seg 3 of 3 Type: Pixel rope segment
Reel: Unassigned

USR2-1

Status: DEFINED

Length: 5,000 mm (196.9") File: 4978 mm | Rounded: 5000 mm
Pixels: 100 Power: 115.2W / 4.80A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL D · Out 1 · USR2 Side: seg 1 of 3 Type: Pixel rope segment
Reel: Unassigned

USR2-2

Status: DEFINED

Length: 5,000 mm (196.9") File: 4978 mm | Rounded: 5000 mm
Pixels: 100 Power: 115.2W / 4.80A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL D · Out 1 · USR2 Side: seg 2 of 3 Type: Pixel rope segment
Reel: Unassigned

USR2-3

Status: DEFINED

Length: 5,000 mm (196.9") File: 4978 mm | Rounded: 5000 mm
Pixels: 100 Power: 115.2W / 4.80A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL D · Out 1 · USR2 Side: seg 3 of 3 Type: Pixel rope segment
Reel: Unassigned

AUD1-1

Status: DEFINED

Length: 8,000 mm (315.0") File: 7976 mm | Rounded: 8000 mm
Pixels: 160 Power: 184.3W / 7.68A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL A · Out 4 · AUD1 Side: seg 1 of 3 Type: Pixel rope segment
Reel: Unassigned

AUD1-2

Status: DEFINED

Length: 10,200 mm (401.6") File: 10160 mm | Rounded: 10200 mm
Pixels: 204 Power: 235W / 9.79A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL A · Out 4 · AUD1 Side: seg 2 of 3 Type: Pixel rope segment
Reel: Unassigned

AUD1-3

Status: DEFINED

Length: 10,200 mm (401.6") File: 10185 mm | Rounded: 10200 mm
Pixels: 204 Power: 235W / 9.79A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL A · Out 4 · AUD1 Side: seg 3 of 3 Type: Pixel rope segment
Reel: Unassigned

AUD2-1

Status: DEFINED

Length: 8,300 mm (326.8") File: 8280 mm | Rounded: 8300 mm
Pixels: 166 Power: 191.2W / 7.97A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL B · Out 4 · AUD2 Side: seg 1 of 3 Type: Pixel rope segment
Reel: Unassigned

AUD2-2

Status: DEFINED

Length: 10,250 mm (403.5") File: 10236 mm | Rounded: 10250 mm
Pixels: 205 Power: 236.2W / 9.84A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL B · Out 4 · AUD2 Side: seg 2 of 3 Type: Pixel rope segment
Reel: Unassigned

AUD2-3

Status: DEFINED

Length: 10,200 mm (401.6") File: 10185 mm | Rounded: 10200 mm
Pixels: 204 Power: 235W / 9.79A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: CTRL B · Out 4 · AUD2 Side: seg 3 of 3 Type: Pixel rope segment
Reel: Unassigned

SPARE-5M-1

SPARE

Status: DEFINED

Length: 5,000 mm (196.9") File: 5000 mm | Rounded: 5000 mm
Pixels: 100 Power: 115.2W / 4.80A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: Spare stock Side: -- Type: Pixel rope segment
Reel: Unassigned Spare For: any 5 m piece (USR)

SPARE-5M-2

SPARE

Status: DEFINED

Length: 5,000 mm (196.9") File: 5000 mm | Rounded: 5000 mm
Pixels: 100 Power: 115.2W / 4.80A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: Spare stock Side: -- Type: Pixel rope segment
Reel: Unassigned Spare For: any 5 m piece (USR)

SPARE-5M-3

SPARE

Status: DEFINED

Length: 5,000 mm (196.9") File: 5000 mm | Rounded: 5000 mm
Pixels: 100 Power: 115.2W / 4.80A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: Spare stock Side: -- Type: Pixel rope segment
Reel: Unassigned Spare For: any 5 m piece (USR)

SPARE-10M-1

SPARE

Status: DEFINED

Length: 10,000 mm (393.7") File: 10000 mm | Rounded: 10000 mm
Pixels: 200 Power: 230.4W / 9.60A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: Spare stock Side: -- Type: Pixel rope segment
Reel: Unassigned Spare For: any 10 m piece (DS/US/AUD-1)

SPARE-10M-2

SPARE

Status: DEFINED

Length: 10,000 mm (393.7") File: 10000 mm | Rounded: 10000 mm
Pixels: 200 Power: 230.4W / 9.60A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: Spare stock Side: -- Type: Pixel rope segment
Reel: Unassigned Spare For: any 10 m piece (DS/US/AUD-1)

SPARE-10M-3

SPARE

Status: DEFINED

Length: 10,000 mm (393.7") File: 10000 mm | Rounded: 10000 mm
Pixels: 200 Power: 230.4W / 9.60A @ 24V Cut Increment: 50mm
Input: NL4 Output: XLR 5-Pin Cable: 12"
Location: Spare stock Side: -- Type: Pixel rope segment
Reel: Unassigned Spare For: any 10 m piece (DS/US/AUD-1)

Status: DEFINED

Length: 11,000 mm (433.1")	File: 11000 mm	Rounded: 11000 mm
Pixels: 220	Power: 253.4W / 10.56A @ 24V	Cut Increment: 50mm
Input: NL4	Output: XLR 5-Pin	Cable: 12"
Location: Spare stock	Side: --	Type: Pixel rope segment
Reel: Unassigned	Spare For: any 11 m piece (AUD-2/3)	

Status: DEFINED

Length: 11,000 mm (433.1")	File: 11000 mm Rounded: 11000 mm	
Pixels: 220	Power: 253.4W / 10.56A @ 24V	Cut Increment: 50mm
Input: NL4	Output: XLR 5-Pin	Cable: 12"
Location: Spare stock	Side: --	Type: Pixel rope segment
Reel: Unassigned	Spare For: any 11 m piece (AUD-2/3)	

Status: DEFINED

Length: 11,000 mm (433.1")	File: 11000 mm Rounded: 11000 mm	
Pixels: 220	Power: 253.4W / 10.56A @ 24V	Cut Increment: 50mm
Input: NL4	Output: XLR 5-Pin	Cable: 12"
Location: Spare stock	Side: --	Type: Pixel rope segment
Reel: Unassigned	Spare For: any 11 m piece (AUD-2/3)	